

Angle grinders

L 1710 FRA

Order no. 259.733



The classical 1400 Watt FLEX with the extra-flat gearbox

A soft start - then full grinding and cutting power. The three-fold full-wave electronic control enables extremely powerful disc control. The tightest corners and areas difficult to access are no longer a problem, thanks to the flat gearbox design.

Technical attributes	L 1710 FRA
Max. disc diameter	125 mm
Speed without load	10000 rpm
Power input	1400 Watt
Power output	880 Watt
Tool fixture	M 14
Weight	2,40 kg

Standard equipment	
1 guard 125 Ø	274.658
1 SoftVib-Handle	316.857

Advantages at a glance

- FLEX three-fold full-wave electronic control: consistent speed control by tachometer generator, soft start, overload protection
- FLEX Motor: designed to handle substantial loads with highest efficiency for powerful output, great endurance thanks to perfect cooling, and air vents aimed to front
- With elastic SoftVib-Handle: greatly reduces the vibration level so the user is subjected to less stress. Also with integrated pin spanner for wrench-free disc changing. It can be fitted on the left or right
- Quick-change guard for universal adjustment. Safety groove prevents the guard from slipping off
- Spindle lock: for easy disc changes
- Gearbox: particularly flat and robust aluminium die-cast construction, accesses all corners
- Quality shut-off carbon brushes: if the carbon brushes wear down, the motor will be automatically switched off and thus protected from damage
- 4 m power cord: with FLEX red plug

Accessories

Steel wire 0,5 mm



Knot-type, mount M 14

Dimensions QTY/PKG: Order no.
in mm:

65 Ø	1	124.524
------	---	---------

125 mm cutting guard



with guide block and 32 mm Ø extraction nozzle for cutting discs with 125 mm Ø for flange without groove

Dimensions QTY/PKG: Order no.
in mm:

125 Ø	1	254.797
-------	---	---------

Angle grinders

Vacuum hose



32 mm internal Ø, 4,0 m long, temperature resistant to 70°C, incl. coupling adapter for vacuum cleaner and 32/28 mm adapter

QTY/PKG: **Order no.**

1 259.630

FixTec quick clamp nut M 14



for tool-free tool changes, approved for discs up to 150 mm Ø

QTY/PKG: **Order no.**

1 313.459

SDS-Clic quick-clamp nut



QTY/PKG: **Order no.**

1 253.049

Small metal carrying case



for all angle grinders with disc Ø up to 125 mm

QTY/PKG: **Order no.**

1 303.224

Angle grinders

SoftVib side handle with pin wrench



The elastic SoftVib side handle is isolated from the machine housing by damping elements, noticeably reducing vibration. for the operator, and with this the risk of vibration-related injuries. With built-in face pin wrench for exchanging the discs quickly without additional tools.

QTY/PKG: Order no.

1 316.857

Steel wire 0,3 mm



Corrugated, mount M 14

Dimensions QTY/PKG: Order no.
in mm:

60 Ø 1 124.516