

Angle grinders

L 3906 C

Order no. 338.605

Advantages at a glance

- Electrical surge protection: for a soft start without power overloading
- The elastic SoftVib side handle is isolated from the machine housing by damping elements, noticeably reducing vibration. for the operator, and with this the risk of vibration-related injuries.
- Rear shaft handle with soft padding for secure grip
- Tool-free adjusting of safety guard
- Optimized dust protection of the motor and the gearbox
- Spindle lock: for easy disc changes
- Handle can be mounted in three positions.
- Quality shut-off carbon brushes: if the carbon brushes wear down, the motor will be automatically switched off and thus protected from damage
- 4 m power cord: with FLEX red plug

The powerful 2100 watt special angle grinder from FLEX

Two hand-angle grinder in new design

Technical attributes	L 3906 C
Max. disc diameter	230 mm
Speed without load	6500 rpm
Power input	2100 Watt
Weight	5,80 kg

Standard equipment	
1 SoftVib-Handle	325.384
1 pin wrench	100.110
1 guard 230 Ø	1 piece

Accessories

SoftVib side handle



The elastic SoftVib side handle is isolated from the machine housing by damping elements, noticeably reducing vibration. for the operator, and with this the risk of vibration-related injuries.

QTY/PKG: Order no.

1 325.384