

Angle grinders

L 3206 CD

Order no. 322.717



Advantages at a glance

- FLEX Motor: designed to handle substantial loads with high efficiency for powerful output, great endurance thanks to perfect cooling, and air vents aimed to front
- FLEX Multi-Grip-System with Vibration damping: front Soft-Vib hand grip can be adjusted in steps up to 180°. With safety locking. The back anti vibration handle can be adjusted 2 x 90° for cutting left and right handed.
- With elastic SoftVib-Handle: greatly reduces the vibration level so the user is subjected to less stress
- Electrical surge protection: for a soft start without power overloading
- Gearbox: particularly flat and robust aluminium die-cast construction
- Quick-release guard: tool-free adjustment
- Spindle lock: for easy disc changes
- 3 point rest: Safe resting for your FLEX
- Quality shut-off carbon brushes: if the carbon brushes wear down, the motor will be automatically switched off and thus protected from damage
- 4 m power cord

The FLEX Red Bear: cutting and grinding made easy

Strong as a Bear 2500 Watt continuous power by 6500 rpm: steel, welding seams and concrete do not stand a chance, because with tough jobs perfect ergonomics are what counts, the RedBear is fitted with the FLEX Multi-Grip and vibration damping system. The side SoftVib Hand grip and the elastic jointed rear handle allows for greatly reduced vibration and more comfortable working, its weight is perfectly balanced.

| Technical attributes | L 3206 CD |
|----------------------|-----------|
| Max. disc diameter | 230 mm |
| Speed without load | 6500 rpm |
| Power input | 2500 Watt |
| Power output | 1700 Watt |
| Tool fixture | M 14 |
| Weight | 6,20 kg |

| Standard equipment | |
|--------------------|---------|
| 1 guard 230 Ø | 265.179 |
| 1 SoftVib-Handle | 325.376 |
| 1 pin wrench | 100.110 |

Accessories

230 mm cutting guard



for drawing and pressure cuts with vacuum set and adjustable support, extraction nozzle with 32 mm outer Ø, collar Ø 62 mm, cut depth 65 mm max., for flange without groove

Dimensions QTY/PKG: Order no.
in mm:

| | | |
|-------|---|---------|
| 230 Ø | 1 | 252.963 |
|-------|---|---------|

Angle grinders

Vacuum hose



32 mm internal Ø, 4,0 m long, temperature resistant to 70°C, incl. coupling adapter for vacuum cleaner and 32/28 mm adapter

QTY/PKG: Order no.

1 259.630

SDS-Clc quick-clamp nut



QTY/PKG: Order no.

1 253.049

Plastic multi-carrying case



Perfect fitting, impact resistant carrying case, universally adaptable for many different FLEX-Maschinen

QTY/PKG: Order no.

1 329.908

SoftVib side handle



The elastic SoftVib side handle is isolated from the machine housing by damping elements, noticeably reducing vibration. for the operator, and with this the risk of vibration-related injuries.

QTY/PKG: Order no.

1 325.376