

Surface finishing Metal and Wood

XS 713

Order no. 334.111



Advantages at a glance

- Anti-slip rubber covered grip, for vibration reduced and tireless working
- Dust-proof on/off switch
- Possible to connect external dust extractor using the supplied as standard adapter

Technical attributes	XS 713
Power input	230 Watt
Power output	75 Watt
Orbit rate, without load	12000 rpm
Orbit	1,6 mm
Sand paper	Ø 125 mm
Sanding media fixing	hook and loop
Weight	1,30 kg

The new handy FLEX rotating-orbital sander

With higher stroke rate and shorter strokes this handy sized machine with its ergonomic grip achieves an evenly smooth surface. The machines low profile allows for extremely sensitive sanding close to the work surface.

Standard equipment	
1 Velcro sand paper, with 8 perforations	1 piece
1 dust bag	332.992
1 adapter for dust extractor	333.026

Accessories

Velcro sanding pad




with 8 perforations

Dimensions QTY/PKG: Order no.
in mm:

125 Ø 1 334.146

Surface finishing Metal and Wood

Velcro sand paper



with 8 perforations

Dimensions in mm:	Grit:	QTY/PKG:	Order no.
125 Ø	grit 40	25	334.308
125 Ø	grit 60	25	334.324
125 Ø	grit 80	25	334.340
125 Ø	grit 100	25	318.027
125 Ø	grit 120	25	317.993
125 Ø	grit 180	25	318.000
125 Ø	grit 220	25	318.019