

Straight grinders

H 1105 VE

Order no. 269.956

Advantages at a glance

- FLEX VE electronic control: variable speed and overload protection
- Quality shut-off carbon brushes: if the carbon brushes wear down, the motor will be automatically switched off and thus protected from damage
- Clamping collar: 40 mm diameter
- Machine length: approx. 330 mm
- Clamping collar length: approx. 53 mm

Low-speed FLEX straight grinder

The low-speed lightweight is ideally suitable for precision grinding in tool and die construction with grinding pins and flap-type grinding wheels up to max. 25 m/sec. Its practical grip cover facilitates extremely sensitive guiding. It can also be used as a support grinder without the grip cover.

Technical attributes	H 1105 VE
Max. disc diameter resin/ceramic up to	30 mm
Max. disc diameter fiber reinforced up to	50 mm
Tool fixture	Ø 3, 1/4", 6, 8 mm
Speed without load	2500-6500 rpm
Power input	710 Watt
Power output	420 Watt
Weight	2,10 kg

Standard equipment

1 collet 6 mm Ø with clamping nut	228.656
1 stopping claw SW 14	254.917
1 open-ended wrench SW 19	104.914

Accessories

Collet



with clamping nut

Dimensions QTY/PKG: Order no.
in mm:

1/4" Ø	1	229.776
6 Ø	1	228.656
3 Ø	1	229.741
8 Ø	1	229.768