

Surface finishing Metal and Wood

LLK 1503 VR

Order no. 315.257



The fillet weld grinder for smooth transitions in tight spots

When weld seam and pipe belt sanders have reached their limits, then it is time for a fillet weld grinder. Its extremely narrow grinding head and flexible FLEX sanding discs can reach most any hard-to-get-at weld seam. For the perfect surface finish on railings, pipe constructions, and other tight spots.

Technical attributes	LLK 1503 VR
Power input	1200 Watt
Power output	700 Watt
Max. disc diameter	152 mm
Speed without load	1500-4700 rpm
Weight	3,40 kg

Standard equipment

1 profiling stone	315.494
1 FixTec quick-clamp nut M 14	313.459
1 compact grinding disc, 3 mm, soft	313.416
1 compact grinding disc, 3 mm, hard	313.424
1 compact grinding disc, 6 mm, soft	313.432
1 compact grinding disc, 6 mm, hard	313.440
1 plastic carrying case with padding	319.082

Advantages at a glance

- 1200 Watt high-power motor: ideal for flexible grinding and polishing of metals and stainless steel to suit the material
- FLEX four-fold full-wave electronics: with speed selection and consistent speed control, soft start, overload protection.
- Slim grinding head: sand and polish with power and ease in tight angles
- FLEX quality sanding discs: made of compressed fleece-fibre nylon
- Profiling stone: for pre-profiling the sanding discs
- Quality shut-off carbon brushes: if the carbon brushes wear down, the motor will be automatically switched off and thus protected from damage
- 4 m power cord: with FLEX red plug
- Heavy-duty carrying case

Accessories

Compact grinding disc



Professional sanding discs: hot-compressed compact sanding discs for stainless steel, metal, and other materials in 2 different thicknesses and hardnesses: the hard sanding disc is used for sanding, the soft one for polishing.

Dimensions Grit: in mm:	QTY/PKG:	Order no.
152 x 3 x 25 soft	1	313.416
152 x 3 x 25 hard	1	313.424
152 x 6 x 25 soft	1	313.432
152 x 6 x 25 hard	1	313.440

Surface finishing Metal and Wood

Profiling stone



for pre-profiling the compact sanding discs

QTY/PKG: Order no.

1 315.494

FixTec quick clamp nut M 14



for tool-free tool changes, approved for discs up to 150 mm Ø

QTY/PKG: Order no.

1 313.459