

## Floor and wall finishing

### MS 1706 FR-Set

Order no. 329.673



#### The new FLEX wall chaser for push and pull cutting

The unique, patented swivel system allows the machine to be used for pull cutting for vertical slots, and push cutting for horizontal slots. Now wall chasing for the laying of cables or conduits is child's play. Cuts two parallel slits up to 35 mm deep and 30 mm wide. When combined with the FLEX S 47 M industrial vacuum cleander gives optimal dust protection for the user even when plunge cutting.

Technical attributes	MS 1706 FR-Set
Cutting depth	0-35 mm
Groove width	10-30 mm
Disc Ø	140 mm
Speed without load	7500 rpm
Power input	1400 Watt
Power output	950 Watt
Tool fixture	M 14
Weight	3,70 kg

#### Standard equipment

Diamantjet VI-Speedcut-cutting disc 140 mm Ø	334.464 (2x)
1 side handle	194.034
1 SDS-Clíc quick-clamp nut M 14	253.049
Distance spacers	318.914 (5x)
Clamping flanges	191.612 (2x)
1 web remover	229.253
1 adapter for dust extractor	327.026
Cable clip	252.188 (3x)
1 plastic carry case	327.034

#### Advantages at a glance

- FLEX four-fold FR electronic control: with consistent speed control by tachometer generator, soft start, overload protection and temperature monitoring
- Rotating motor allows for push and pull cutting
- Optimal dust extraction and maximum safety due to enclosed guard
- Toolless blade changing and slit width adjustment
- Rotating adaptor for dust extractor
- Adjustable cutting depth
- Plunge cut stop
- Quality shut-off carbon brushes: if the carbon brushes wear down, the motor will be automatically switched off and thus protected from damage
- Complete kit: with plastic carrying case and 2 Diamond Jet VI-Speedcut discs for rapid cutting of masonry, limestone, concrete and porous concrete

## Floor and wall finishing

### Accessories

#### Diamantjet VI - Speedcut




For cuts in walls, limestone, concrete and gas concrete. Thanks to the innovative HDS (high density sintered) technology, which can be recognised by the high density and homogeneity of the binding components, the Speedcut cutting disc stands out due to its uniform willingness to cut, its long life span and the overheating protection it offers. Due to the ribbed cover, only minimal pressure needs to be applied and the swarf is removed quickly: the workpiece is sliced through cleanly and smoothly.

Dimensions in mm:	QTY/PKG:	Order no.
----------------------	----------	-----------

140 Ø	1	334.464
-------	---	---------

#### Sharpening stone for diamond tools



Dimensions in mm:	QTY/PKG:	Order no.
----------------------	----------	-----------

320 x 160 x 30	1	251.756
-------------------	---	---------