

Saws

CSM 4060

Order no. 307.815



The versatile metal circular saw for dry cuts

For fast, clean cuts through pipes, threaded rods, profiles, cable ducts, corrugated and trapezoidal sheet metal, sandwich boards and much more. With integrated chip collection compartment.

Technical attributes	CSM 4060
Blade Ø	185 mm
Saw blade drill Ø	20 mm
Max. cutting depth (90°)	0-63 mm
Max. material thickness in steel 400 N/mm ²	6 mm
Max. material thickness in aluminium 250 N/mm ²	10 mm
Speed without load	3800 rpm
Power input	1400 Watt
Power output	720 Watt
Weight	5,40 kg

Standard equipment

Carbide tipped saw blades for steel, 38 teeth (185 x 312.304 (2x) 20 mm)

1 parallel stop 312.312

1 ring / open-ended wrench 312.347

1 plastic carry case 1 piece

Advantages at a glance

- 1400 Watt high-power motor: for precise cuts without coolant
- Spindle lock: for quick and easy changing of the saw blade
- Depth-adjustable saw foot for stepless setting of the cutting depth up to 63 mm for precise cuts
- Chip collection compartment with view window: large capacity, for a clean, chip-free work place
- Extensive selection of standard equipment with 2 carbide-tipped saw blades, assembly tools and edge guide
- Special carbide-tipped saw blades: nearly burr-free cuts, trimming threaded bars possible without recutting the thread
- Heavy-duty carrying case

Accessories

Carbide tipped saw blade for steel



enables a practically burr-free cut, no touching up is necessary

Dimensions Teeth: QTY/PKG: Order no.
in mm:

185 Ø x 20 38 1 312.304