

Core drill technology

BHW 1549 VR

Order no. 299.197



The FLEX blind hole drill with integrated water supply

The water supply is integrated into the gearbox of this drill. This cools the diamond drill bit optimally and flushes away the drilling sludge. Perfect holes can be drilled in concrete and stone in next to no time. Tilting is avoided, thanks to the low structural silhouette. It can also be used with the FLEX pressurised water tank.

Technical attributes	BHW 1549 VR
Power input	1200 Watt
Power output	700 Watt
Speed under load	3000-9000 rpm
Speed without load	3500-10000 rpm
Tool fixture	M 14
Diamond drill Ø	5-10 mm
Weight	3,30 kg

Standard equipment

1 bail handle	236.934
1 open-ended wrench SW 17	106.461
1 splash guard	255.171
1 GFCI operator protection circuit breaker in cord	257.373
1 metal carrying case	273.686

Advantages at a glance

- FLEX triple VR electronics: with consistent speed control by tachometer generator, overload protection, and speed selection
- Quick-action, brass coupling: for 1/2" water hoses
- Tool fixture: M 14 for 5-10 mm Ø diamond blind hole drills
- GFCI operator protector circuit breaker: integrated in cord
- Quality shut-off carbon brushes: if the carbon brushes wear down, the motor will be automatically switched off and thus protected from damage

Accessories

Diamond blind hole drill bit



M 14, wet, for natural stone

D in mm:	T in mm:	L in mm:	QTY/PKG:	Order no.
5 Ø	25	60	1	250.491
6 Ø	50	80	1	250.492
8 Ø	50	80	1	250.493
10 Ø	50	80	1	250.494

Core drill technology

Sharpening stone for diamond tools



Dimensions in mm:	QTY/PKG:	Order no.
----------------------	----------	-----------

320 x 160 x 30	1	251.756
-------------------	---	---------