

Mixers

RZ 600 VV

Order no. 282.413



Advantages at a glance

- FLEX four-fold full-wave electronic control: with consistent speed control, soft start with acceleration trigger, overload protection and speed pre-selection with adjusting wheel
- With 2 mixing heads: I and II
- Mixing head adapter: 2 x 16 mm Ø with keyway
- Protection frame
- Quality shut-off carbon brushes: if the carbon brushes wear down, the motor will be automatically switched off and thus protected from damage
- not suitable for use in explosive environments

The FLEX double positive mixer

This powerful mixer operates with two counter-rotating mixing heads. These counter external torque, making it easy to guide. Mixtures are also mixed particularly thoroughly. Ideal for tough adhesive, insulating material, multi-component resins, varnish and paint. Thanks to the speed pre/selection, it can be adjusted optimally to any material. The speed is slowly boosted by the acceleration trigger and prevents splashing.

Technical attributes	RZ 600 VV
Speed without load	0-400 rpm
Power input	1300 Watt
Power output	850 Watt
Tool fixture	2 x 16 mm Ø
Clamping neck Ø	63 mm
Max. mixing head Ø	130 mm
Weight	6,30 kg

Standard equipment	
1 handle (long)	257.580
Mixing head I and II	252.200

Accessories

Mixing head I and II, galvanized version



Ideal for tough mixtures, adhesive, dual and multi-component resins and plastics, varnish and paint, sealing and insulation material, coating material, ready-mixed mortar, plaster, concrete adhesive, etc. Counter-active mixing: Both mixing heads mesh and blend the mixture with particular intensity. Equipment: - Supplied in pairs, adapted for the FLEX positive mixer. For insertion in the positive mixer guides. - 600 mm overall length Please note: the mixing head with marking ring is inserted in fixture I, the mixing head with two marking rings in fixture II.

Mixing head in mm:	Mixture in kg:	QTY/PKG:	Order no.
130 Ø	5 - 60	1	252.200